

WHICH KENWOOD PROTALK[®] RADIO IS RIGHT FOR YOU?

Compare top features for these popular models of these ProTalk business two-way radios.



PKT-300



NX-P1302AUK



NX-P1300AUK



NX-P1300NUK

| | | | | |
|--------------------------------|--------------------------------|--|--|---|
| Motorola Equivalent | CLS-xxxx, CLP-xxxx | RMUxxxx, RMVxxxx, RMMxxxx | RDUxxxx, RDVxxxx | XPR-xxxx, CP200D, CP100D |
| Power Output | 2W UHF | 2W UHF* | 5W UHF* | 5W UHF* |
| Max Channels | 16 | 64 | 64 | 64 |
| Number of Zones | 0 | 4 | 4 | 4 |
| Battery Life | 14 hours | 12 hours | 12 hours | 12 hours |
| Battery Saver | ✓ | ✓ | ✓ | ✓ |
| Battery mAh Rating | 2,200 mAh/ 2,550 mAh Li-Ion | 2,000 mAh/ 2,550 mAh Li-Ion | 2,000 mAh/ 2,550 mAh Li-Ion | 2,000 mAh/ 2,550 mAh Li-Ion |
| Cloning | ✓ | ✓ | ✓ | ✓ |
| Military Specifications | Mil-Std 810, C, D, E, F, G, H | Mil-Std 810, C, D, E, F, G | Mil-Std 810, C, D, E, F, G | Mil-Std 810, C, D, E, F, G |
| IP Rating | IP52/55 | IP54/55 | IP54/55 | IP54/55 |
| Analog | ✓ | ✓ | ✓ | ✓ |
| Digital | N/A | Upgrade to digital with license key | Upgrade to digital with license key | ✓ NXDN or DMR • Group / Individual Call • Site Roaming • Remote Stun / Kill, Monitor, Check & Control |
| IS Option | | | | ✓ |
| Range | 270,000sq ft, 23 floors | 270,000sq ft, 23 floors | 450,000sq ft, 42 floors | 550,000sq ft, 50 floor |
| Warranty | 2 Year | 3 Year | 3 Year | 3 year |

* VHF models available